




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> :  G03B 27/73	A1	(11) International Publication Number: WO 92/05470  (43) International Publication Date: 2 April 1992 (02.04.92)
(21) International Application Number: PCT/US91/06577 (22) International Filing Date: 13 September 1991 (13.09.91) (30) Priority data: 583,740                      17 September 1990 (17.09.90) US (71) Applicant: EASTMAN KODAK COMPANY [US/US]; 343 State Street, Rochester, NY 14650 (US). (72) Inventors: COSGROVE, Patrick, Andre ; 82 Troutbeck Lane, Rochester, NY 14626 (US). GOODWIN, Robert, Melvin ; 29 Tree Brook Drive, Rochester, NY 14625 (US). KWON, Heemin ; 58 Bromley Road, Pittsford, NY 14534 (US). SCALISE, Anthony ; 24 Lower Hills Lane, Fairport, NU 14450 (US).		(74) Agent: SUGAS, Edward; 343 State Street, Rochester, NY 14650-2201 (US). (81) Designated States: AT (European patent), BE (European patent), CA, CH (European patent), DE (European pa- tent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (Euro- pean patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>

(54) Title: USER-INTERACTIVE REDUCTION OF SCENE BALANCE FAILURES



## (57) Abstract

A photofinishing image processing operator detects failures in the performance of a scene balance mechanism on a digitized image and enables a photofinisher to interactively correct for such failures before the failed image has been processed and an unacceptable output image printed. Whenever a failed image is identified, one or more reasonably low resolution versions of the image as processed by the scene balance mechanism are displayed to the photofinishing operator, together with a request for image adjustment information that is used to modify or correct the color balance of the image. In response to this user input information, the image processor adjusts color balance parameters of the scene balance mechanism, so that the digitized image processed by the modified scene balance mechanism will yield a print of acceptable color balance quality. This interaction of the photofinishing operator with the image processing system may be accomplished by way of several modes, including displaying differently processed versions of the image, or a single version of the image processed by the scene balance mechanism, together with a question regarding the type of image. The failure detection mechanism preferably employs a non-linear discriminator, such as a neural network.

BEST AVAILABLE COPY

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU <sup>+</sup>	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE*	Germany	MC	Monaco	US	United States of America
DK	Denmark				

+ Any designation of "SU" has effect in the Russian Federation. It is not yet known whether any such designation has effect in other States of the former Soviet Union.

**USER-INTERACTIVE REDUCTION OF SCENE  
BALANCE FAILURES**

**FIELD OF THE INVENTION**

5           The present invention relates in general to digitized color imagery photofinishing systems and is particularly directed to a mechanism for detecting failures in the performance of an image adjustment (e.g. scene balance) mechanism and, in response to a  
10 detected potential failure, interactively adjusting color balance control parameters of the image adjustment mechanism, so as to enable that digitized color image to be modified or corrected (e.g. color balanced) in a manner that will produce a  
15 representation that is pleasing to the human visual system.

**BACKGROUND OF THE INVENTION**

20           Optical photofinishing systems customarily employ some form of image correction or adjustment mechanism, such as a scene balance mechanism, which evaluates the content of each digitized image and selectively adjusts or modifies the image, for example adjusts its color balance, so that, when reproduced, as  
25 by way of an optical printer, the printed image will be a high quality color reproduction that is pleasing to the human visual system. For purposes of the present invention, by 'scene balance mechanism' is meant an adjustment of image color balance based upon the scene  
30 content and the sensitometric characteristics (e.g. exposure, light source, etc.) of the image being reproduced. Adjustment of 'color balance' is defined as adjusting the average red, green and blue image levels, so as to ensure that an image will have the appropriate  
35 color and neutral reproduction characteristics.

Unfortunately, because such image adjustment mechanisms are typically statistically based, some images will be unsuccessfully treated and, consequently, will yield an unacceptable reproduction. Moreover, depending upon the particular image correction mechanism employed, the rate at which images are unsuccessfully processed can be significant (e.g. on the order of five percent). In those instances where the correction mechanism fails to properly correct the image (e.g. adjust its color balance), either the customer receives a poor quality print or the photofinisher discovers the mistake and then manually corrects the image. In either case (in response to a disgruntled customer or a predelivery intercept during a photofinisher's review), because the error is not corrected until after the image is printed, the photofinisher incurs a substantial cost in materials (the print paper being a major portion of the cost of film processing) and time (due to the break in the flow of the image reproduction process).

#### SUMMARY OF THE INVENTION

In accordance with the present invention, rather than simply tolerate a failure in the performance of the image correction mechanism and manually correct the improperly processed image after an unacceptable print has been discovered, an image adjustment failure detection mechanism is inserted into the photofinishing process upstream of the reproduction (printing) stage, in order to identify those images where the image correction mechanism is likely to fail. Once such a 'likely to fail' image is identified, one or more reasonably low resolution versions of the digitized image, produced as a result of modifications

or parameter corrections of the adjustment mechanism are displayed to the photofinisher, together with a request for the photofinisher to input image adjustment information that is used to modify or correct (the  
5 color balance of) the image. In response to this user input information, the image processor adjusts parameters of the image correction mechanism, so that the digitized image processed by the selected  
10 (modified) image adjustment mechanism will yield a reproduction (print) of acceptable color balance quality. This interaction of the photofinishing operator with the image processing system may entail several modes. Where the image adjustment mechanism is a scene balance mechanism for balancing the color  
15 content of the image, each mode serves to modify control parameters of the scene balance operation.

In accordance with a first mode, plural, low resolution versions of the processed image of  
20 acceptable presentation quality are displayed on the photofinisher's workstation display. One of these image versions (e.g. one that has been centrally placed within an array of images across the display) shows how the digitized image would appear based upon the current  
25 response of the image adjustment (scene balance) mechanism. Displayed versions of the image on opposite sides of this one image show variations in color balance resulting from iteratively shifted parameter adjustments to the (scene balance) mechanism (e.g.  
30 lighter and darker where the failure mode detected is one of neutral balance). By way of a display prompt, the photofinisher is requested to choose from among the different displayed versions of the image the one that is most pleasing. In response to this selection, the  
35 manner in which the scene balance mechanism processes

the digitized image is modified to conform with the color balance characteristics of the selected image version.

5                   Pursuant to a second mode of operation, which is similar to the first mode, the user is given a choice of only two versions of the image - the one currently produced by the scene balance mechanism and an alternative that is based upon a set of modified  
10 parameters. As in the first mode, the digitized image is then processed to conform with the color balance characteristics of the selected image version, indicating one of two possible scene interpretations, such as flash vs. non-flash or color- subject failure  
15 vs. non-subject failure.

                  In accordance with a third mode of operation, a low resolution version of the image processed by the scene balance mechanism is displayed to the  
20 photofinishing operator, together with a question regarding the type of image, e.g. whether or not the image is a backlit scene or a flash scene, which may seem similar to the scene balance mechanism but require different balance processing. The photofinisher's  
25 response is then employed to refine how the scene balance mechanism corrects the image (e.g. corrects for an illumination ambiguity).

                  The mechanism for detecting failures in the  
30 performance of the scene balance mechanism may comprise a statistically based, linear discriminator, such as a Fischer Discriminant or a Bayes Classifier, which employ a multidimensional discrimination space derived from predictors computed from the imagery data.  
35 Preferably, however, the failure detection mechanism

employs a non- linear discriminator, such as a back propagation-trained neural network, because of its ability to accurately recognize images that the scene balance mechanism will correctly process. Typically, both linear discriminators and neural networks will detect potential color balance failures for about 50% of poor quality images; however, the preferred neural network-based failure discriminator will effectively never detect a potential failure for a correctly color-balanced image.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 diagrammatically illustrates a photographic color film photofinishing minilab with which the image adjustment (e.g. scene balance) failure detection and correction mechanism of the present invention may be employed;

Figure 2 diagrammatically shows an example of a neural network-configured scene balance failure discriminator containing a feed-forward n-layer perceptron (trained by back propagation);

Figure 3 illustrates a first 'sliding scale' mode of the failure detection and interactive correction process according to the present invention;

Figure 4 illustrates a second mode of the failure detection and interactive correction process according to the present invention in which a photofinishing minilab operator is given a choice of two differently scene balance processed versions of an image;

Figure 5 diagrammatically illustrates a third mode of operation of the scene balance failure discriminator, wherein a low resolution version of the image processed by the scene balance mechanism is displayed to the photofinishing operator, together with a question regarding the type of image; and

Figure 6 diagrammatically illustrates a multiregion map used to define the characteristics of a scene balance failure discriminator.

#### DETAILED DESCRIPTION

Before describing in detail the image adjustment failure discrimination mechanism in accordance with the present invention, it should be observed that the present invention resides primarily in a novel structural combination of conventional digital imagery processing circuits and components and not in the particular detailed configurations thereof. Accordingly, the structure, control and arrangement of these conventional circuits and components have been illustrated in the drawings by readily understandable block diagrams which show only those specific details that are pertinent to the present invention, so as not to obscure the disclosure with structural details which will be readily apparent to those skilled in the art having the benefit of the description herein. Thus, the block diagram illustrations of the Figures do not necessarily represent the mechanical structural arrangement of the exemplary system, but are primarily intended to illustrate the major structural components of the system in a convenient functional grouping, whereby the present invention may be more readily understood.

35



Figure 1 diagrammatically illustrates a photographic color film processing system (e.g. photofinishing minilab) with which the image adjustment failure discriminator in accordance with the present invention may be employed and, for purposes of the present description, such a system may be of the type described in co-pending Patent application Serial Number \_\_\_, filed \_\_\_, by S. Kristy, entitled "Multi-resolution Digital Imagery Photofinishing System", assigned to the assignee of the present application and the disclosure of which is incorporated herein. It should be observed, however, that the system described in the above-referenced co-pending Kristy application is merely an example of one type of system in which the invention may be used and is not to be considered limitative of the invention. In general, the invention may be incorporated in any digitized imagery processing and reproduction system. Moreover, although, in the description to follow, the failure discriminator will be described in terms of the operation of a scene balance mechanism, it should be observed that the principles presented here are applicable to other image adjustment schemes.

In accordance with the digital image processing system of Figure 1, photographic color images, such as a set of twenty-four or thirty-six 36mm-by-24mm image frames of a 35mm film strip 10, are scanned by a high resolution opto-electronic color film scanner 12, such as a commercially available Eikonix Model 1435 scanner. High resolution film scanner 12 outputs digitally encoded data representative of the response of its imaging sensor pixel array (e.g. a 3072 x 2048 pixel matrix) onto which a respective photographic image frame of film strip 10 has been

projected by an input imaging lens system. This digitally encoded data, or 'digitized' image, is encoded to some prescribed resolution (e.g. 16 bits per color per pixel) that encompasses a range of values over which the contents of the scene on the color film may vary. For a typical color photographic negative, the range of values is less than the density vs. exposure latitude of the film, but is sufficiently wide to encompass those density values that can be expected to be encountered for a particular scene. Then, by means of a scene balancing mechanism resident in an attendant image processing workstation 14, which contains a frame store and image processing application software through which the digitized image may be processed to achieve a desired base image appearance and configuration, the digitized image is mapped into a set of lower bit resolution digital codes (e.g. 8 bits per color per pixel), each of which has a resolution corresponding to the dynamic range of a digitized image data base (e.g. frame store), the contents of which may be adjusted in the course of driving a reproduction device 16, for example, enabling a print engine to output a high quality color print.

Preferably, the digitized imagery data output by the high resolution film scanner is subjected to a code conversion mechanism of the type described in co-pending application Serial No. \_\_\_, filed \_\_\_, by Y. Madden et al, entitled "Extending Dynamic Range of Stored Image Database," assigned to the assignee of the present application and the disclosure of which is herein incorporated. Pursuant to this code conversion scheme, the dynamic range of the digitized image database is extended so as to permit shifting of encoded pixel values without 'clipping', and to provide

a limited window of values into which extremely high reflectance image points may be encoded and stored. Digital codes into which the image scanner output are mapped by the scene balance mechanism are converted  
5 into a set of reduced-range digital codes of the same resolution as, but having a smaller range of image content values than the dynamic range of the digitized image data base. The code conversion mechanism operates to convert a maximum value of 100% white reflectance to  
10 an encoded value that is less than the upper limit of the dynamic range of the database to accommodate shifts in the digitized imagery data and allow for the placement of specular highlights that are beyond the 100% white reflectance maximum.

15

In accordance with the imagery data processing system described in the above referenced co-pending Kristy application, each high resolution captured image is stored as a respective image data  
20 file containing a low, or base, resolution image bit map file and a plurality of higher resolution residual images associated with respectively increasing degrees of image resolution. By iteratively combining these higher resolution residual images with the base  
25 resolution image, successively increased resolution images may be recovered from the base resolution image.

As an example, spatial data values representative of a high resolution (3072 x 2048) image  
30 scan of a 36mm-by- 24mm image frame of a 35mm film strip 10 may be stored as a respective image data file including a base resolution image bit map file containing data values associated with a spatial image array or matrix of 512 rows and 768 columns of pixels  
35 and an associated set of residual image files to be

stored on the disc. Within the workstation itself, the base resolution image may be further sub-sampled to derive an even lower resolution sub-array of image values (e.g. on the order of 128 x 192 pixels) for use  
5 by the photofinishing operator in the course of formatting and storing a digitized image file.

Pursuant to the present invention, a substantially reduced resolution version of each  
10 digitized image to be color balance-processed by the scene balance mechanism is also coupled to a scene balance failure discriminator, which determines the likelihood that the output image processed by the scene balance mechanism will be of acceptable color balance  
15 quality. For this purpose, the scene balance mechanism failure discriminator examines the spatial content of a very small sub-array (e.g. 24 x 36 pixels) produced by subsampling compression of a 128 x 192 pixel version of the image of interest and, based upon a previously  
20 generated statistical model of prescribed characteristics of the image, derives a measure of the likelihood that the color balance performance of the scene balance mechanism for that image will produce a visually acceptable reproduction (high resolution  
25 output print).

The discriminator, per se, may comprise a statistically based, linear discriminator, such as a Fischer Discriminant or a Bayes Classifier, which use a  
30 multidimensional discrimination space derived from predictors computed from the imagery data. Preferably, however, the failure detection mechanism employs a non-linear discriminator, such as a back propagation-trained neural network, because of its ability to  
35 accurately recognize images that will be correctly

-11-

processed by the scene balance mechanism. Namely, although both linear discriminators and neural networks are capable of detecting color balance failures for about 50% of the images that will fail ('bad' images),  
5 a linear discriminator will also erroneously flag failures for some images that will be correctly processed by the scene balance mechanism. On the other hand, the preferred neural network-based failure discriminator will effectively never detect a scene  
10 balance failure for a 'good' image.

The substantially reduced resolution version of the image, such as one comprising a pixel sub-array in the order of only 24x36 pixels, contains sufficient  
15 spatial color content to permit identification of scene balance failures for a high resolution image, but with considerably reduced computational intensity. Still, even with such a reduced image size, the number of values (864 for a 24 x 36 pixel sub-array) that enter  
20 into the statistical analysis is still substantial and, for a linear discriminator, may have an associated set of approximately 50 statistical measures (predictors) of the content of the scene. For the same sized image sub- array, it is possible to build a back propagation  
25 neural network that operates on a reasonably constrained set of parameters.

As one non-limitative example, a neural network, such as that diagrammatically shown in Figure  
30 2 as a feed-forward n-layer perceptron (trained by back propagation), may be configured of a nine element input layer 31, a twelve element hidden layer and a single element output layer 33. An image training population on the order of several thousand 24x36 pixel scenes  
35 repeatedly and successively applied to the network may

be used to load the network. As a non-limitative example, a set of nine predictors (Nos. 1-9) listed in Table 1, below and referencing the region map of Figure 6, may be employed. It should be observed, however, that other predictors in addition to and different from those listed here, may be used. For a discussion of the use of neural networks for pattern recognition and choosing predictors, attention may be directed to the text: "Adaptive Pattern Recognition and Neural Networks", by Yoh-Haw Pao, Chapters 1, 2 and 5.

TABLE 1

<u>PREDICTOR</u>	<u>DEFINITION</u>
No. 1	Red maximum of region 5 - red average of entire frame.
No. 2	Red maximums of regions 3, 4, 5 are averaged together and the red average of the entire frame is subtracted from it.
No. 3	Variance of neutral T space value for entire range, where T space is defined, for example, as set forth in U.S. Patents Nos. 4,159,174 and 4,933,709).
No. 4	Neutral T space average of entire frame.
No. 5	Hyperbolic tangent of center maximum, minus the center average.
No. 6	Neutral T space average of region 5 minus neutral T space average of regions 1, 2, 3, 4.
No. 7	Average of neutral T space maximums of regions 3, 4, 5 minus neutral T space average of entire frame.
No. 8	Neutral T space centroid of entire frame.
No. 9	Green magenta average of entire frame.

-13-

Moreover, the type of neural network employed is not constrained to a feed-forward, back propagation implementation. Other network types, such as a counter  
5 propagation network may be used. Suffice it to say that examples given here have been shown to correctly identify scene balance failures for approximately 50% of 'bad' images (images for which the scene balance mechanism will fail) but 0% of 'good' images, namely  
10 those images for which the scene balance mechanism will produce a properly color-balanced output image. For a further discussion of neural networks in general and their application to statistical processing, attention may be directed to the text: "Parallel Distributed  
15 Processing" Vol. I-II, by McClelland, Rumelhart and PDP Research Group, MIT Press, 1988.

The scene balance failure detection mechanism of the present invention is preferably incorporated  
20 within the image processing software employed by workstation 14, in order that those images where the scene balance mechanism is likely to fail will be identified and corrected prior to the reproduction (printing) stage of the photofinishing process. Once  
25 such a scene balance failure image is identified, one or more reasonably low resolution versions of the digitized image processed by the scene balance mechanism are displayed to the photofinishing operator, together with a request for the photofinishing operator  
30 to input image adjustment information that is used to modify or correct the color balance action of the scene balance mechanism on that image. In response to this user input information, the image processor adjusts color balance parameters of the scene balance  
35 mechanism, so that the resulting processed image will

produce a print of acceptable color balance quality. This interaction of the photofinishing operator with the image processing system may be accomplished using any one of several modes diagrammatically illustrated in Figure 3-5, described below.

More particularly, Figure 3 illustrates a first mode of the failure detection and interactive correction process according to the present invention in which a plurality of low resolution (128 x 192 pixels) images 20-1, 20-2, 20-3, ..., 20-N, each of which is a respectively different version of the (128 x 192) digitized image as processed by the resident scene balance mechanism, are displayed as a linear array on the photofinisher's workstation display. The image that results from the application of the currently defined scene balance mechanism to the scanned image may correspond to image 20-3, centrally placed within a linear array of images across the workstation display screen. Images 20-1, 20-2 and images 20-4 and 20-5 on opposite sides of this image have respectively different variations in color balance obtained by successively offsetting or shifting the scene balance mechanism along a prescribed axis (e.g. lighter and darker scan densities where the failure mode detected is one of neutral balance). Further variations in the image may be formed by the use of a conventional graphics processing scrolling operator to effectively create a 'sliding scale' for a linear array of images that may be panned across the screen.

By way of a display prompt, the photofinishing operator is requested to choose the most visually pleasing one of the different versions of the image within the display window associated with



-15-

respectively different biasing of the scene balance mechanism. In response to this selection, the manner in which the scene balance mechanism processes the digitized image is modified to conform with the color balance characteristics of the selected image version. For this purpose, the bias settings employed to produce the selected image are used to modify the scene balance mechanism. Namely, since each image version represents a prescribed offset or shift of the scene balance mechanism, selecting a given image effectively specifies the magnitude of the offset bias to be used by the scene balance mechanism in processing the high resolution image for storage and subsequent reproduction.

Figure 4 illustrates a second mode of the failure detection and interactive correction process according to the present invention in which the photofinishing minilab operator is given a choice of only two versions of the image. As shown in the figure, on the workstation display two low resolution images 41 and 42, each of which is a respectively different version of the (128 x 192) digitized image as processed by the resident scene balance mechanism, are displayed on the photofinisher's workstation display. One of the displayed images has been processed as though the image is front-lit (e.g. by a flash illumination source), while the other displayed image has been processed as though the image is back-lit (silhouette). Both types of images look similar to the scene balance mechanism, but require different processing. The photofinisher's choice of which displayed version of the image is most pleasing determines which version of the scene balance mechanism will be used to process that image.

35

Figure 5 diagrammatically illustrates a third mode of operation of the scene balance failure discriminator, wherein a low resolution version 51 of the image processed by the scene balance mechanism is displayed to the photofinishing operator, together with a panel 52 containing a question regarding the type of image, e.g. whether or not the image is backlit or a flash scene. The photofinisher's input response to the displayed question panel 52 (e.g. by mouse or keyboard entry) is then employed by the image processing software to refine how the scene balance mechanism corrects the image (e.g. corrects for an ambiguity in the type of scene illumination). For example, for the case where the photofinisher enters the fact that the subject/scene is backlit, a scene balance mechanism optimized for a silhouette is employed. Similarly, for the case where the photofinisher enters the fact that the subject/scene is illuminated by a flash source, a scene balance mechanism optimized for a front-lit image is used.

As will be appreciated from the foregoing description, the present invention provides a technique for detecting images prone to scene balance failures and enabling the photofinisher to interactively correct for failures in the performance of the scene balance mechanism before an image has been processed and an unacceptable output image printed. By correcting for a discovered scene balance failure prior to printing the image, the photofinisher will not incur what can amount to substantial penalties in terms of cost of materials and film processing time.

Moreover, the present invention offers the advantage that, by using a failure discriminator, only

-17-

some, but not all, of the scenes need to be evaluated by the photofinisher. Without it, to detect as many failures as possible, the photofinisher would have to look at every image.

5

While we have shown and described an embodiment in accordance with the present invention, it is to be understood that the same is not limited thereto but is susceptible to numerous changes and modifications as known to a person skilled in the art, and we therefore do not wish to be limited to the details shown and described herein but intend to cover all such changes and modifications as are obvious to one of ordinary skill in the art.

15

WHAT IS CLAIMED

1. For use with an image processing system, in which a color photographic image that has been  
5 captured on a color photographic image recording medium is digitally encoded by an opto-electronic device and stored in a digital data base as a digitized image, said digitized image being processed by means of an  
10 image adjustment mechanism to derive a modified output image to be coupled to an image reproduction device, a method of controlling the operation of said system to reduce the effects of failures in the processing of a digitized image by said image adjustment mechanism comprising the steps of:

15 (a) processing said digitized image in accordance with an image adjustment failure discriminator to define the likelihood of whether or not said image adjustment mechanism will cause said output image to be reproduced as a prescribed quality  
20 image; and

(b) in response to a prescribed likelihood that said image adjustment mechanism will fail to cause said output image to be reproduced as said prescribed quality image, generating a request for user-sourced  
25 control information for modifying the manner in which said image adjustment mechanism processes said image.

2. A method according to claim 1, wherein step (b) comprises, in response to a prescribed  
30 likelihood that said image adjustment mechanism will fail to cause said image to be reproduced as said prescribed quality image, displaying an image representative of the effect of the processing of said image by said image adjustment mechanism and generating  
35 a request for user-sourced control information for

-19-

controllably modifying the manner in which said image adjustment mechanism processes said image.

3. A method according to claim 1, wherein  
5 step (b) comprises, in response to a prescribed likelihood that said image adjustment mechanism will fail to cause said image to be reproduced as said prescribed quality image, displaying a plurality of  
10 images representative of the effects of different processing of said image by modified versions of said image adjustment mechanism and generating a request for a user-sourced selection of one of said displayed images, in response to which said image adjustment mechanism is controllably adjusted to process said  
15 image as an acceptable quality output image for reproduction.

4. A method according to claim 1, wherein  
said image adjustment mechanism comprises a scene  
20 balance mechanism which processes a digitized image to derive a color content-balanced output image.

5. A method according to claim 1, wherein  
said image adjustment mechanism failure discriminator  
25 is implemented as a statistical linear discriminator.

6. A method according to claim 1, wherein  
said image adjustment mechanism failure discriminator  
is implemented as a non-linear discriminator.  
30

7. A method according to claim 1, wherein  
said image adjustment mechanism failure discriminator  
is implemented as a neural network.

35

8. A method according to claim 7, wherein said neural network is a back propagation-trained neural network.

5 9. A method according to claim 1, wherein step (b) comprises displaying an image representative of the effect of processing said digitized image by said image adjustment mechanism and generating a request for the inputting of information representative  
10 of a characteristic of said image, in response to which said image adjustment mechanism is controllably adjusted to process said image as an acceptable quality output image for reproduction.

15 10. A method according to claim 1, wherein step (a) comprises coupling a reduced resolution version of said digitized image to said image adjustment mechanism failure discriminator in order to define the likelihood of whether or not said image  
20 adjustment mechanism will cause said output image to be reproduced as a prescribed quality image.

11. For use with an image processing system, in which a color photographic image that has been  
25 captured on a color photographic image recording medium is digitally encoded by an opto-electronic device and stored in a digital data base as a digitized image, said digitized image being processed by means of an image adjustment mechanism to derive a modified output  
30 image to be coupled to an image reproduction device, a method of controlling the operation of said system to reduce the effects of failures in the processing of a digitized image by said image adjustment mechanism comprising the step of:

35

-21-

(a) prior to reproducing said image, examining said image and determining the likelihood of whether or not said image adjustment mechanism will cause said output image to be reproduced as a  
5 prescribed quality image.

12. A method according to claim 11, further including the step of:

(b) in response to a prescribed likelihood  
10 that said image adjustment mechanism will fail to cause said output image to be reproduced as said prescribed quality image, modifying said image adjustment mechanism.

15 13. A method according to claim 12, wherein step (b) comprises, in response to a prescribed likelihood that said image adjustment mechanism will fail to cause said image to be reproduced as said prescribed quality image, displaying an image  
20 representative of the effect of the processing of said digitized image by said image adjustment mechanism and generating a request for control information for controllably modifying the manner in which said image adjustment mechanism processes said digitized image.

25 14. A method according to claim 12, wherein step (b) comprises, in response to a prescribed likelihood that said image adjustment mechanism will fail to cause said image to be reproduced as said  
30 prescribed quality image, displaying a plurality of images representative of the effects of different processing of said digitized image by modified versions of said image adjustment mechanism and generating a request for a selection of one of said displayed  
35 images, in response to which said image adjustment

mechanism is controllably adjusted to process said image as an acceptable quality output image for reproduction.

5           15. A method according to claim 11, wherein said image adjustment mechanism comprises a scene balance mechanism which processes an image to derive a color content- balanced output image.

10           16. A method according to claim 11, wherein said image adjustment mechanism failure discriminator is implemented as a statistical linear discriminator.

15           17. A method according to claim 11, wherein said image adjustment mechanism failure discriminator is implemented as a non-linear discriminator.

20           18. A method according to claim 15, wherein step (a) comprises coupling the contents of said digitized image to a neural network-implemented scene balance mechanism failure discriminator.

25           19. A method according to claim 18, wherein said neural network is a back propagation-trained neural network.

30           20. A method according to claim 11, wherein step (b) comprises displaying an image representative of the effect of processing said digitized image by said image adjustment mechanism and generating a request for the inputting of information representative of a characteristic of said image, in response to which said image adjustment mechanism is controllably adjusted to process said image as an acceptable quality  
35   output image for reproduction.



21. A method according to claim 11, wherein  
step (a) comprises coupling a reduced resolution  
version of said digitized image to said image  
5 adjustment mechanism failure discriminator in order to  
define the likelihood of whether or not said image  
adjustment mechanism will cause said output image to be  
reproduced as a prescribed quality image.

10 22. For use with an image processing system,  
in which a color photographic image that has been  
captured on a color photographic image recording medium  
is digitally encoded by an opto-electronic device and  
stored in a digital data base as a digitized image,  
15 said digitized image being processed by means of an  
image adjustment mechanism to derive a modified output  
image to be coupled to an image reproduction device, a  
method of controlling the operation of said system to  
reduce the effects of failures in the processing of a  
20 digitized image by said image adjustment mechanism  
comprising the step of:

displaying an image representative of the  
effect of the processing of said digitized image by  
said image adjustment mechanism and generating a  
25 request for control information for controllably  
modifying the manner in which said image adjustment  
mechanism processes said digitized image.

23. A method according to claim 22, wherein  
30 said step comprises displaying a plurality of images  
representative of the effects of different processing  
of said digitized image by modified versions of said  
image adjustment mechanism and generating a request for  
a selection of one of said displayed images, in  
35 response to which said image adjustment mechanism is

controllably adjusted to process said image as an acceptable quality output image for reproduction.

24. A method according to claim 22, wherein  
5 said step comprises displaying an image representative of the effect of processing said digitized image by said image adjustment mechanism and generating a request for the inputting of information representative of a characteristic of said image, in response to which  
10 said image adjustment mechanism is controllably adjusted to process said image as an acceptable quality output image for reproduction.

25. A method according to claim 22, wherein  
15 said image adjustment mechanism comprises a scene balance mechanism which processes a digitized image to derive a color content-balanced output image.

26. A method according to claim 22, wherein  
20 said image adjustment mechanism failure discriminator is implemented as a statistical linear discriminator.

27. A method according to claim 22, wherein  
said image adjustment mechanism failure discriminator  
25 is implemented as a non-linear discriminator.

28. A method according to claim 22, wherein  
said image adjustment mechanism failure discriminator  
is implemented as a neural network.

30

29. A method according to claim 28, wherein  
said neural network is a back propagation-trained  
neural network.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



# INTERNATIONAL SEARCH REPORT

International Application No PCT/US 91/06577

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (if several classification symbols apply, indicate all) <sup>6</sup> According to International Patent Classification (IPC) or to both National Classification and IPC <b>IPC5: G 03 B 27/73</b>											
<b>II. FIELDS SEARCHED</b> <div style="text-align: right; margin-right: 100px;">Minimum Documentation Searched<sup>7</sup></div> <table style="width: 100%; border: none;"> <tr> <td style="width: 20%; border: none;">Classification System</td> <td style="border: none;">Classification Symbols</td> </tr> <tr> <td style="border: none; height: 40px; vertical-align: bottom;">IPC5</td> <td style="border: none; vertical-align: bottom;">G 03 B</td> </tr> </table> <div style="text-align: center; margin-top: 10px;">Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched<sup>8</sup></div>			Classification System	Classification Symbols	IPC5	G 03 B					
Classification System	Classification Symbols										
IPC5	G 03 B										
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup></b> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Category *</th> <th style="width: 60%;">Citation of Document,<sup>11</sup> with indication, where appropriate, of the relevant passages<sup>12</sup></th> <th style="width: 30%;">Relevant to Claim No.<sup>13</sup></th> </tr> </thead> <tbody> <tr> <td style="vertical-align: top;">X  A</td> <td style="vertical-align: top;">DE, A1, 3824096 (FUJI PHOTO FILM CO. LTD) 26 January 1989, see column 10 - column 15  --</td> <td style="vertical-align: top;">1,2,4, 11,22  3,5-10, 12-21, 23-29</td> </tr> <tr> <td style="vertical-align: top;">X  A</td> <td style="vertical-align: top;">DE, A1, 3642821 (FUJI PHOTO FILM CO., LTD.) 19 June 1987, see column 4 - column 16  --</td> <td style="vertical-align: top;">1-4,9- 15,20- 25 5-8,16- 19,26- 29</td> </tr> </tbody> </table>			Category *	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>	X  A	DE, A1, 3824096 (FUJI PHOTO FILM CO. LTD) 26 January 1989, see column 10 - column 15  --	1,2,4, 11,22  3,5-10, 12-21, 23-29	X  A	DE, A1, 3642821 (FUJI PHOTO FILM CO., LTD.) 19 June 1987, see column 4 - column 16  --	1-4,9- 15,20- 25 5-8,16- 19,26- 29
Category *	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>									
X  A	DE, A1, 3824096 (FUJI PHOTO FILM CO. LTD) 26 January 1989, see column 10 - column 15  --	1,2,4, 11,22  3,5-10, 12-21, 23-29									
X  A	DE, A1, 3642821 (FUJI PHOTO FILM CO., LTD.) 19 June 1987, see column 4 - column 16  --	1-4,9- 15,20- 25 5-8,16- 19,26- 29									
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p>* Special categories of cited documents:<sup>10</sup></p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 48%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p> </div> </div>											
<b>IV. CERTIFICATION</b> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none; vertical-align: top;"> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <b>Date of the Actual Completion of the International Search</b>  <b>4th February 1992</b> </div> <div style="border: 1px solid black; padding: 5px;"> <b>International Searching Authority</b>  <b>EUROPEAN PATENT OFFICE</b> </div> </td> <td style="width: 50%; border: none; vertical-align: top;"> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <b>Date of Mailing of this International Search Report</b>  <div style="text-align: center; font-size: 1.2em;">20.02.92</div> </div> <div style="border: 1px solid black; padding: 5px;"> <b>Signature of Authorized Officer</b>  <div style="text-align: center; font-size: 0.8em;">M. M. van der Drift</div> </div> </td> </tr> </table>			<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <b>Date of the Actual Completion of the International Search</b>  <b>4th February 1992</b> </div> <div style="border: 1px solid black; padding: 5px;"> <b>International Searching Authority</b>  <b>EUROPEAN PATENT OFFICE</b> </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <b>Date of Mailing of this International Search Report</b>  <div style="text-align: center; font-size: 1.2em;">20.02.92</div> </div> <div style="border: 1px solid black; padding: 5px;"> <b>Signature of Authorized Officer</b>  <div style="text-align: center; font-size: 0.8em;">M. M. van der Drift</div> </div>							
<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <b>Date of the Actual Completion of the International Search</b>  <b>4th February 1992</b> </div> <div style="border: 1px solid black; padding: 5px;"> <b>International Searching Authority</b>  <b>EUROPEAN PATENT OFFICE</b> </div>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <b>Date of Mailing of this International Search Report</b>  <div style="text-align: center; font-size: 1.2em;">20.02.92</div> </div> <div style="border: 1px solid black; padding: 5px;"> <b>Signature of Authorized Officer</b>  <div style="text-align: center; font-size: 0.8em;">M. M. van der Drift</div> </div>										

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No
X A	DE, A1, 3719716 (FUJI PHOTO FILM CO., LTD.) 17 December 1987, see column 4 - column 18	1-4,9- 15,20- 25 5-8,16- 19,26- 29
X A	EP, A2, 0327112 (FUJI PHOTO FILM CO., LTD.) 9 August 1989, see column 3 - column 13	1-4,9- 15,20- 25 3-8,16- 19,26- 29
A	US, A, 4685071 (LEE) 4 August 1987, see the whole document	1-29
A	US, A, 4642684 (ALKOFER) 10 February 1987, see the whole document	1-29
A	US, A, 4677465 (ALKOFER) 30 June 1987, see the whole document	1-29
A	US, A, 4845551 (MATSUMOTO) 4 July 1989, see column 4 - column 7; figures 5-9	1-29
A	DE, A1, 3437069 (AGFA-GEVAERT AG) 10 April 1986, see the whole document	1-29
A	EP, A1, 0054848 (FOTOMEC-SAN MARCO S.P.A.) 30 June 1982, see the whole document	1-29



**ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.PCT/US 91/06577**

SA 52955

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.  
The members are as contained in the European Patent Office EDP file on 31/10/91  
The European Patent office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
DE-A1- 3824096	26/01/89	JP-A-	1019336	23/01/89
		US-A-	4942462	17/07/90
		JP-A-	1035542	06/02/89
		JP-A-	1077382	23/03/89
-----				
DE-A1- 3642821	19/06/87	JP-A-	62141530	25/06/87
		US-A-	4782390	01/11/88
-----				
DE-A1- 3719716	17/12/87	GB-A-B-	2191655	16/12/87
		JP-A-	62293889	21/12/87
		US-A-	4797712	10/01/89
-----				
EP-A2- 0327112	09/08/89	JP-A-	1200879	14/08/89
		US-A-	4991004	05/02/91
		JP-A-	1200880	14/08/89
-----				
US-A- 4685071	04/08/87	EP-A-B-	0218628	22/04/87
		JP-T-	62500325	05/02/87
		WO-A-	86/05643	25/09/86
-----				
US-A- 4642684	10/02/87	EP-A-B-	0221133	13/05/87
		JP-T-	62500747	26/03/87
		WO-A-	86/06850	20/11/86
-----				
US-A- 4677465	30/06/87	EP-A-B-	0250468	07/01/88
		JP-T-	63501251	12/05/88
		WO-A-	87/02852	07/05/87
-----				
US-A- 4845551	04/07/89	JP-A-	61275625	05/12/86
-----				
DE-A1- 3437069	10/04/86	DE-A-	3564870	13/10/88
		EP-A-B-	0177857	16/04/86
		JP-A-	61091647	09/05/86
		US-A-	4704026	03/11/87
-----				
EP-A1- 0054848	30/06/82	AT-E-T-	10789	15/12/84
		CH-A-B-	651403	13/09/85
		WO-A-	82/02257	08/07/82

For more details about this annex : see Official Journal of the European patent Office, No. 12/82

EPO FORM P0479

**This Page Blank (uspto)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**This Page Blank (uspto)**